



Product data sheet

Power tools for trade & industry

Cordless Combi

PRO GSB 120-LI



Highly flexible, highly economical

The most important data

Torque (soft/hard/max.)	14/30/- Nm
No-load speed (1st gear / 2nd gear)	0 – 400 / 0 – 1,500 rpm

Order number 0 601 9G8 1L1

Technical data

Additional data

Torque (soft/hard/max.)	14/30/- Nm
No-load speed (1st gear / 2nd gear)	0 – 400 / 0 – 1,500 rpm
Weight excl. battery	0.9 kg
Torque settings	20+2
Battery type	Lithium-Ion
Max. impact rate	22,500 bpm
Chuck capacity, min./max.	0.8 / 10 mm

Noise/vibration information

Drilling in metal

Vibration emission value ah	1.5 m/s ²
Uncertainty K	1.4 m/s ²

Impact drilling in masonry

Vibration emission value ah	10.2 m/s ²
Uncertainty K	1.5 m/s ²

Screwdriving

Vibration emission value ah	1.5 m/s ²
Uncertainty K	0.8 m/s ²

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Power and flexibility within reach for screwdriving and drilling
- 2-speed gearbox enables high productivity and excellent torque
- Electronic Cell Protection for longer battery life and more durability



You can find more information about the deviations in the following link: <https://www.bosch-professional.com/my/en/wac/>

