

SP 16.000 DIRT

The SP 16.000 Dirt dirty water pump pumps up to 16,000 liters of dirty water per hour and is equipped with a height-adjustable float switch.



Order no.

1.645-830.0

- Max. flow rate < 16,000 l/h, delivery height 8 m, pressure up to max. 0.8 bar
- Ceramic slide ring sealing, float switch, Quick Connect adapter
- Hose connection piece

Technical data

EAN code		4054278951683
Rated input power	W	550
Max. flow rate	l/h	< 16000
Delivery temperature	°C	max. 35
Delivery head	m	8
Pressure	bar	max. 0.8
Grain size	mm	max. 20
Immersion depth	m	max. 7
Min. residual water, manual	mm	25
Residual water height	mm	25
Connection thread		G1 1/2
Pressure-side connection thread		G1/2 internal thread
Power cable	m	10
Voltage	V	230 - 240
Frequency	Hz	50
Colour		Yellow
Weight without accessories	kg	4.9
Weight incl. packaging	kg	5.7
Dimensions (L x W x H)	mm	229 x 238 x 303

Scope of supply

Hose connection piece: G1, 1", 1 1/4", 1 1/2"

Equipment

Comfortable carrying handle

Easy hose connection thanks to Quick Connect


Switching between manual/automatic operation: Possibility of fixing the float switch

Flexible, height-adjustable float switch

In automatic operation (auto), the pump automatically switches with the water level

In manual operation, the pump runs continuously to ensure the minimum quantity of residual water

Ceramic face seal.



Ceramic face seal.

- For an extra long lifetime.



Height-adjustable float switch

- Increases the flexibility when setting the switch-on and switch-off point of the pumps and prevents dry running.



Quick Connect

- Connection thread for quickly and simply connecting 1", 1 1/4" and 1 1/2" hoses or a G1 connection.

ACCESSORIES FOR SP 16.000 DIRT

1.645-830.0



		Order no.	Description	
ADAPTERS / CONNECTORS				
Pump adapter including check valve, small	1	6.997-359.0	Pump adapter with check valve for vacuum-resistant connection of suction hoses to pumps (e.g. garden pumps and high-pressure pumps for domestic use).	☐
FILTER				
Prefilter for submersible pumps, small	2	2.997-201.0	Protects the submersible pump from clogging: prefilter for SP 9.000 to SP 16.000 Flat/Dirt and SP 1 to SP 5 Flat/Dirt submersible pumps.	☐
MISCELLANEOUS				
Fabric hose set	3	2.997-100.0	Space-saving hose set with a flexible fabric hose, including stainless steel hose clamp for connecting to submersible pumps. Ideal as a feed hose for water removal in the event of flooding.	☐
HOSES				
PrimoFlex® hose 1" 1 m	4	2.645-247.0	The PrimoFlex® 1" quality garden hose is available by the metre, meaning it can be ordered in exactly the length you require (max. 50 m). With pressure-resistant reinforcement mesh. Contains no substances that are harmful to health.	☐
Hose Performance Plus 3/4" -25m	5	2.645-322.0	The Performance Plus garden hose (3/4", 25 m) has a kink-resistant multi-layer fabric with anti-UV & anti-algae protection. Designed for 30 bar burst pressure (-20 to +60 °C). 15-year guarantee.	☐
Hose Performance Plus 3/4" -50m	6	2.645-323.0	The Performance Plus garden hose (3/4", 50 m) has a kink-resistant multi-layer fabric with anti-UV & anti-algae protection. Designed for 30 bar burst pressure (-20 to +60 °C). 15-year guarantee.	☐
PrimoFlex® hose 3/4" - 25 m	7	2.645-142.0	The flexible PrimoFlex® garden hose (3/4", 25 m) with pressure-resistant reinforcement is suitable for watering fruit, vegetables, and ornamental plants. Burst pressure: 24 bar.	☐

☐ Available accessories.