# Product Datasheet

# G7321 3/8” Air Impact Wench

KOBE GREEN LINE professional air tool ergonomically designed with operator friendly features for improved comfort throughout longer periods of use

## Features and Benefits:

- Twin hammer mechanism
- Maximum bolt capacity M14 (9/16”)
- One finger start/stop trigger operation
- 4 point adjustable air (speed) regulator
- Forward/reverse speed regulator
- Lightweight composite body reduces the effects of vibration and hand chill
- Downward facing external exhaust in handle

| **FORWARD** |
|---|
| Position 1: 8000 rpm |
| Position 2: 9100 rpm |
| Position 3: 10,100 rpm |
| **REVERSE** |
| 10,200 rpm |

## Typical Applications:

- Suitable for light workshop and garage use

## Specifications:

| | | | |
|---|---|---|---|
| Order Code | **KBE2705820K** | Air Inlet Thread | ¼” NPT |
| Drive Size | 3/8” | Minimum Hose Size | 3/8” (10mm) |
| Max. Free Speed | 10,200 rpm | Sound Pressure Level | 88 dBA |
| Max. Torque (10 Sec) | 393 Nm | Vibration Level | 4.9 m/s² |
| Working Torque (5 sec) | 339 Nm | Overall Length | 165 mm |
| Recommended Air Pressure | 6.2 bar (90psi) | Weight | 1.3 Kg |
| Air Consumption | 3 cfm (85 L/min) | | |

## Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)

- EN ISO 11148-9:2011 / Hand-held non-electric power tools - Safety requirements Part 6: Assembly power tools for threaded fasteners

- ISO 28927-12:2012 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 7: Wrenches, screwdrivers and nut runners with impact, impulse or ratchet action

- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT
©Copyright 2020 – The Kennedy Group Ltd