KOBE

CE

Product Datasheet

DAR1510 10mm Reversible Air Angle Drill

KOBE RED LINE professional air tools offering a high standard and superb value combined with the design elements of a modern industrial classic.

Features and Benefits:

- Industrial quality Jacobs chuck
- Fingertip control of reverse action for easy directional change
- Rear exhaust directs air away from the workpiece
- Compact low profile head (overall head height 94mm with chuck jaws extended)
- Supplied with chuck Key



Typical Applications:

- Ideal for drilling and screwdriving in confined areas

Specifications:

Order Code	**KBE2701425M**	Minimum Hose Size	3/8” (10mm)
Free Speed	1,800 rpm	Sound Pressure Level	90 dBA
Chuck Capacity	10 mm	Sound Power Level	97 dBA
Spindle Size	3/8” x 24	Vibration Level	0.5 m/s²
Recommended Air Pressure	6.2 bar (90psi)	Vibration Uncertainty K	0.3 m/s²
Air Consumption	4 cfm (113 L/min)	Overall Length	205 mm
Air Inlet Thread	¼” NPT	Weight	1.1 Kg

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)
- EN ISO 11148-3:2012 / Hand-held non-electric power tools - Safety requirements - Part 3: Drills and tappers (ISO 11148-3:2012)
- EN ISO 28927-5:2009 Hand-held portable power tools - Test methods for evaluation of vibration emission Part 5: Drills and impact drills (ISO 28927-5:2009)
- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code - Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT

©Copyright 2020 – The Kennedy Group Ltd