Product Datasheet

DS4510L 10mm Straight Air Drill

KOBE RED LINE professional air tools offering a high standard and superb value combined with the design elements of a modern industrial classic.

Features and Benefits:

- Safety release lever throttle prevents accidental start-ups
- Industrial Jacobs keyed chuck
- High performance
- Planetary gearing
- Stall resistant
- Lightweight



Typical Applications:

- Used in automotive, production or general maintenance applications
- Ideal for vertical drilling
- Drilling in hard to reach confined areas

Specifications:

Order Code	**KBE2701450N**	Minimum Hose Size	3/8” (10mm)
Free Speed	4,500 rpm	Sound Pressure Level	100 dBA
Chuck Capacity	10 mm	Sound Power Level	103 dBA
Spindle	3/8” x 24	Vibration Level	2.5 m/s^2
Recommended Air Pressure	6.2 bar (90psi)	Vibration Uncertainty K	0.45 m/s^2
Air Consumption	4 cfm (113 L/min)	Overall Length	190 mm
Air Inlet Thread	¼” NPT	Weight	0.9 kg

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)
- EN ISO 11148-3:2012 / Hand-held non-electric power tools - Safety requirements - Part 3: Drills and tappers (ISO 11148-3:2012)
- EN ISO 28927-5:2009 Hand-held portable power tools - Test methods for evaluation of vibration emission Part 5: Drills and impact drills (ISO 28927-5:2009)
- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT
©Copyright 2020 – The Kennedy Group Ltd