Product Datasheet

GDA2203 90° Angle Air Die Grinder

KOBE RED LINE professional air tool offering a high standard and superb value combined with the design elements of a modern industrial classic.

Features and Benefits:

- Precision geared or longer life and smoother running
- Safety lever throttle prevents accidental start-ups
- Ideal for tight access applications
- Rear exhaust directs away from the workpiece
- Supplied with two collet spanners and a comprehensive instruction
- Lightweight durable aluminium alloy housing



Typical Applications:

- For use on grinding, polishing, buffing and deburring
- Ideal for cleaning, Smoothing welds seams and castings
- Maintenance applications

Specifications:

Order Code	**KBE2702020H**	Minimum Hose Size	3/8" (10mm)
Free Speed	22,000 rpm	Sound Pressure Level	90 dBA
Collet Size	6 mm	Sound Power Level	97 dBA
Motor Power	0.3 hp	Vibration Level	1.24 m/s²
Recommended Air Pressure	6.2 bar (90psi)	Vibration Level Uncertainty K	0.74 m/s²
Air Consumption	4 cfm (113 L/min)	Overall Length	155 mm
Air Inlet Thread	¼" NPT	Weight	0.5 Kg

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)

- EN ISO 11148-4:2012 / Hand-held non-electric power tools - Safety requirements Part 9: Die grinders (ISO 11148-9:2011)

- EN ISO 28927-10:2011 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 12: Die grinders

- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT
©Copyright 2020 – The Kennedy Group Ltd