KOBE

CE

Product Datasheet

GD2206L 6mm Air Die Grinder

KOBE RED LINE professional air tool offering a high standard and superb value combined with the design elements of a modern industrial classic.

Features and Benefits:

- Powerful 0.5hp motor for a good surface finish
- Safety release throttle prevents accidental start-ups
- Lightweight durable aluminium alloy housing
- Rear exhaust directs away from the workpiece
- Kit Includes straight die grinder with 3 and 6mm collets, collet spanner, 10 assorted mounted points in a robust blow moulded case



Typical Applications:

- For use on grinding, polishing, buffing and deburring
- Ideal for cleaning, Smoothing welds seams and castings
- Maintenance applications

Specifications:

Order Code	**KBE2702030L**	Minimum Hose Size	3/8" (10mm)
Free Speed	23,000 rpm	Sound Pressure Level	88.72 dBA
Collet Size	6 mm, 3 mm	Sound Power Level	dBA
Motor Power	0.5 hp	Vibration Level	11.33 m/s²
Recommended Air Pressure	6.2 bar (90psi)	Vibration Level Uncertainty K	1.385 m/s²
Air Consumption	4 cfm (113 L/min)	Overall Length	172 mm
Air Inlet Thread	¼" NPT	Weight	0.6 Kg

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)

- EN ISO 11148-4:2012 / Hand-held non-electric power tools - Safety requirements Part 9: Die grinders (ISO 11148-9:2011)

- EN ISO 28927-10:2011 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 12: Die grinders

- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT

©Copyright 2020 – The Kennedy Group Ltd