# Product Datasheet

## NB160 High Performance Air Nibbler - Pull Type

KOBE RED LINE professional air tool offering a high standard and superb value combined with the design elements of a modern industrial classic

### Features and Benefits:

- Powerful ½" HP motor
- Produces burr free cuts without distortion
- Built-in regulator matches speed to application
- Teasing throttle for precise control
- Down facing exhaust clear debris from the work area
- Forward, reverse, left and right cutting positions
- Supplied with the up cut punch and die




### Typical Applications:

- Ideal for body shop and sheet metal work

### Specifications:

| | | | |
|---|---|---|---|
| Order Code | **KBE2703400K** | Minimum Hose Size | 3/8" (10mm) |
| Cutting Capacity Steel | 1.2mm | Sound Pressure Level | 96.63 dBA |
| Cutting Capacity Aluminium | 2 mm | Sound Power Level | 107.63 dBA |
| Cutting Speed | 2.6 MPA | Vibration Level | 8.65 m/s² |
| Recommended Air Pressure | 6.2 bar (90psi) | Vibration Level Uncertainty K | 1.35 m/s² |
| Air Consumption | 4 cfm (113 L/min) | Overall Length | 180 mm |
| Air Inlet Thread | ¼" NPT | Weight | 0.98 Kg |

### Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)

- EN ISO 11148-4:2012 / Hand-held non-electric power tools - Safety requirements Part 4: Non-rotary percussive power tools (ISO 11148-4:2012)

- EN ISO 28927-10:2011 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 7: Nibblers and shears (ISO 28927-7:2009)

- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT
©Copyright 2020 – The Kennedy Group Ltd