

Product Datasheet

CSP005s – Automatic Shut-off Air Screwdriver 0.6 - 5.1 Nm

KOBE BLUE LINE professional air tool with a higher specification offering maximum user comfort and durability - designed for extensive periods of heavy duty use in a production environment

Features and Benefits:

- Push to start type with auto shut-off clutch for precision applications
- 3 interchangeable torque springs allow for easy conversion for new applications
- External torque adjustment does not require disassembly of the tool
- Variable speed throttle
- Soft ergonomic grip for operator comfort
- Forward / reverse control on top for easy access
- Handle exhaust directs air away from the workpiece and operator
- Hanging ring included



Typical Applications:

- Heavy duty reverse action pistol grip screwdriver suitable for production assembly applications

Specifications:

Order Code	KBE2703760K	Sound Pressure Level	84 dBA
Hex Drive Capacity	¼"	Sound Power Level	93 dBA
Free Speed	600 rpm	Vibration Level	0.5 m/s ²
Recommended Air Pressure	6.2 bar (90psi)	Vibration Level Uncertainty K	0.3m/s ²
Air Consumption	4 cfm (113 L/min)	Overall Length	235 mm
Air Inlet Thread	¼" NPT	Weight	0.8 Kg
Minimum Hose Size	3/8" (10mm)		

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)
- EN ISO 11148-4:2012 / Hand-held non-electric power tools - Safety requirements
Part 6: Assembly power tools for threaded fasteners (ISO 11148-6:2010)
- EN ISO 28927-10:2011 / Hand-held portable power tools - Test methods for evaluation of vibration emission
Part 2: Wrenches, nut runners and screwdrivers (ISO 28927-2:2009)
- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code
Engineering method (grade 2) (ISO 15744:2002)