KOBE

CE

Product Datasheet

SS1525K Stainless Steel ¼” Straight Air Screwdriver Kit

KOBE RED LINE professional air tool offering a high standard and superb value combined with the design elements of a modern industrial classic.



Features and Benefits:

- Adjustable clutch
- Fingertip control of reverse action with lock
- ¼” hex bit size
- Ball retainer mechanism for easy bit change
- Rear exhaust directs away from the work area
- Kit contains:

SS1525s Air Screwdriver, 3 Clutch springs
No.1 Crosspoint double ended bit 65mm
5mm slotted bit 50mm
2x spanners, Clutch adjusting hex wrench
¼” NPT nipple, Mini oil bottle
Robust moulded case



Typical Applications:

- Ideal tool for general maintenance applications, assembly and refurbishing

Specifications:

Order Code	**KBE2703800K**	Minimum Hose Size	3/8” (10mm)
Free Speed	1,500 rpm	Sound Pressure Level	77 dBA
Capacity	¼” Hex	Sound Power Level	89 dBA
Torque Range	0.3 – 0.7 Nm	Vibration Level	1.0 m/s²
Recommended Air Pressure	6.2 bar (90psi)	Vibration Level Uncertainty K	0.6 m/s²
Air Consumption	4 cfm (113 L/min)	Overall Length	220 mm
Air Inlet Thread	¼” NPT	Weight	0.6 Kg

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)
- EN ISO 11148-4:2012 / Hand-held non-electric power tools - Safety requirements Part 6: Assembly power tools for threaded fasteners (ISO 11148-6:2010)
- EN ISO 28927-10:2011 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 2: Wrenches, nut runners and screwdrivers (ISO 28927-2:2009)
- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT

©Copyright 2020 – The Kennedy Group Ltd