KOBE

CE

Product Datasheet

SP1825K Pistol Air Screwdriver Kit

Features and Benefits:



- Adjustable clutch
- Torque range 3 -8 Nm (30–70 in/lbs)
- High speed operation
- Robust Aluminium body and steel clutch housing
- ¼" female quick change toolless chuck
- Convenient single handed forward / reverse
- In-handle exhaust
- Kit includes hexagon wrench and spanner,

No.1, 2 and 3 x 50mm cross point bits,
No.4, 5 and 6mm x 50mm slotted bits,
No.2 x 100mm cross point double-ended bit.

Typical Applications:

- Ideal tool for general maintenance applications, assembly and refurbishing

Specifications:

Order Code	**KBE2703850K**	Sound Pressure Level	90.55 dBA
Capacity	¼" Hex	Sound Power Level	
Free Speed	1,800 rpm	Vibration Level	11.33 m/s²
Recommended Air Pressure	6.2 bar (90psi)	Vibration Level Uncertainty K	1.385m/s²
Air Consumption	4 cfm (113 L/min)	Overall Length	178 mm
Air Inlet Thread	¼" NPT	Weight	0.9 Kg
Minimum Hose Size	3/8" (10mm)		

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)
- EN ISO 11148-4:2012 / Hand-held non-electric power tools - Safety requirements Part 6: Assembly power tools for threaded fasteners (ISO 11148-6:2010)
- EN ISO 28927-10:2011 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 2: Wrenches, nut runners and screwdrivers (ISO 28927-2:2009)
- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT

©Copyright 2020 – The Kennedy Group Ltd