Product Datasheet

R5228 13mm Mini Belt Air Sander

Features and Benefits:

- Sanding arm can be rotated to any angle to improve access in confined spaces
- Ergonomic and comfortable rubber grip for reduced vibration
- Low profile teasing throttle with safety bar for precise speed control
- Adjustable air speed regulator
- Quick and easy belt change
- Directional rear exhaust
- Spare belt and hex wrench included



Typical Applications:

- Suitable for deburring, sanding and finishing applications on flat, concave and convex surfaces

Specifications:

Order code	**KBE2704270K**	Sound Pressure Level	85.54 dBA
Belt Size	610 mm x 13 mm	Sound Power Level	96.54 dBA
Free Speed	20,000 rpm	Vibration Level	0.66 m/s²
Recommended Air Pressure	6.2 bar (90psi)	Vibration Level uncertainty K	0.56 m/s²
Air Consumption	4.2 cfm (119 L/min)	Overall length	463 mm
Air Inlet Thread	¼" NPT	Folded Length	310 mm
Minimum Hose Size	3/8" (10mm)	Weight	0.95 Kg

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)
- EN ISO 11148-8:2011 / Hand-held non-electric power tools - Safety requirements Part 8: Sanders and polishers (ISO 11148-8:2011)
- EN ISO 28927-3:2009 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 3: Polishers and rotary, orbital and random orbital sanders (ISO 28927-3:2009)
- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT
©Copyright 2020 – The Kennedy Group Ltd