

# ROAIRVAC VACUUM PUMP

## **Two-stage rotary vane pump.**

Compact, portable device for vacuum and cleansing of refrigeration systems of all kinds.


## Key features:

- Magnetic safety valve to protect the refrigeration cycle from oil contamination during power outage
- Vacuum meter with integrated drag indicator enables simple and fast control of the vacuum process
- Gas ballast valve for reduction of water vapour in the oil container
- Increased torque for longer service life, due to 4-pole motor (1.5 and 3.0 models only)
- Specially designed filter reduces oil mist on nozzle
- Gauge-glass enables easy oil level monitoring
- Thermal switch protects unit from overheating

• **Ergonomic Handle**  
/ Light, compact and easy to



## Education with Conventional Technology



$\frac{1}{4}$ " SAE standard connection, with  
adaptor for  $\frac{5}{16}$ " and  $\frac{3}{8}$ " SAE

Practical operating instructions  
always easily visible

**Proven Ability. New Solutions.**

**Phone: 1800 186 657, Fax: 1800 286 657  
www.rothenberger.com.au**

## ROAIRVAC VACUUM PUMP

### Two-stage rotary vane pump.

Compact, portable device for vacuum and cleansing of refrigeration systems of all kinds.

	ROAIRVAC 1.5	ROAIRVAC 3.0	ROAIRVAC 6.0	ROAIRVAC 9.0
Part No.	R170061	R170062	R170063	R170064
Pump Rating	1.5CFM / 42l/min	3.0CFM / 85l/min	6.0CFM / 170l/min	9.0CFM / 255l/min
Vacuum Stages	2	2	2	2
Poles	4	4	2	2
Final Vacuum	25micron / 0.034mbar	25micron / 0.034mbar	25micron / 0.034mbar	25micron / 0.034mbar
Motor Rating	0.25HP / 190W	0.33HP / 250W	0.5HP / 375W	1.0HP / 750W
Voltage	230V	230V	230V	230V
Frequency	50~60Hz	50~60Hz	50~60Hz	50~60Hz
Connections	1/4" SAE	1/4" SAE	1/4" SAE	1/4" SAE
- with adaptor	5/16" SAE 3/8" SAE	5/16" SAE 3/8" SAE	5/16" SAE 3/8" SAE	5/16" SAE 3/8" SAE
Oil Capacity	250ml	330ml	330ml	590ml
Weight	9.0kg	10.7kg	11.5kg	17.0kg
Pressure Gauge	50mm	50mm	50mm	50mm

### The ROAIRVAC Vacuum Pump Range:



ROAIRVAC 1.5



ROAIRVAC 6.0



ROAIRVAC 3.0



ROAIRVAC 9.0