

## Product Datasheet

### GES2506L - 6 mm Extended Spindle Air Die Grinder

KOBE RED LINE professional air tool offering a high standard and superb value combined with the design elements of a modern industrial classic.

#### Features and Benefits:

- Extended spindle allowing two-handed operation
- Safety release throttle prevents accidental start-ups
- Front exhaust blows away dust and debris
- Fitted with long collet nut
- Supplied with two collet spanners and a comprehensive instruction manual



#### Typical Applications:

- Suitable for use on a wide range of applications with an extended spindle for extra reach in hard to reach areas
- For use on grinding, polishing, buffing and deburring
- Ideal for cleaning, Smoothing welds seams and castings
- Maintenance applications

#### Specifications:

Order Code	<b>KBE2702040N</b>	Sound Pressure Level	93 dBA
Collet Size	6 mm	Sound Power Level	103 dBA
Free Speed	25,000 rpm	Vibration Level	4.65 m/s <sup>2</sup>
Recommended Air Pressure	6.2 bar (90psi)	Vibration Uncertainty K	0.49 m/s <sup>2</sup>
Air Consumption	4 cfm (113 L/min)	Overall Length	248 mm
Air Inlet Thread	1/4" NPT	Weight	0.85 Kg
Minimum Hose Size	3/8" (10mm)		

#### Standards:

- EN ISO 12100:2010 / Safety of machinery -General principles for design - Risk assessment and risk reduction (ISO 12100:2010)
- EN ISO 11148-9:2011 / Hand-held non-electric power tools - Safety requirements Part 9: Die grinders (ISO 11148-9:2011)
- ISO 28927-12:2012 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 12: Die grinders
- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)