

Product Datasheet

IW750 - 3/4" Square Drive Air Impact Wrench

3/4" heavy duty air impact wrench with a one-piece aluminium housing offering high durability and operator comfort.

Features and Benefits:

- High-low power regulator
- Maximum bolt size: M24 (7/8")
- One handed easy push button for forward-reverse operation
- Finger throttle lever



Typical Applications:

- The IW750 is ideal for tightening/loosening of wheel bolts, truck and bus maintenance, farm machinery, and construction equipment.

Specifications:

Order Code	KBE2702325S	Air Inlet Thread	1/4" NPT
Drive Size	3/4"	Minimum Hose Size	3/8" (10mm)
Free Speed	4,800 rpm	Sound Pressure Level	86 dBA
Maximum Torque	1085 Nm	Sound Power Level	
Working Torque	949 Nm	Vibration Level	5.8 m/s ²
Recommended Air Pressure	6.2 bar (90psi)	Overall Length	248 mm
Air Consumption	4.2 cfm (198 L/min)	Weight	4.6 Kg

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)
- EN ISO 11148-9:2011 / Hand-held non-electric power tools - Safety requirements Part 6: Assembly power tools for threaded fasteners (ISO 11148-6:2010)
- EN ISO 28927-2:2009 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 2: Wrenches, nut runners and screwdrivers (ISO 28927-2:2009)
- EN ISO 15744:2008 / Hand-held non-electric power tools Noise measurement code - Engineering method (grade 2) (ISO 15744:2002)